



## TECHNICAL DATA SHEET

Revision: October 8, 2019

### RockRidge Brown-Fused Aluminum Oxide

Product: Brown-Fused Aluminum Oxide- Blasting Grain

Description: Aluminum Oxide is manufactured in an electric arc furnace that produces an extremely tough, long-lasting grain which is graded to macrogrit exacting standards. It may be repeatedly recirculated and is chemically stable and not affected by alkalis, acids, or harmful atmospheres.

Applications: Aluminum Oxide is suitable for wet or dry surface preparation, cleaning, deburring, and cutting of various metals, ceramics, glass, wood, rubber, plastic, stone, and composite materials.

#### Typical Physical Characteristics:

Crystal Form	Alpha-Alumina
True Density	3.95 g/cm <sup>3</sup>
Hardness	Knoop (100) 2500 kg/mm, Mohs 9.0
Melting Point	2000°C
Color	Brown- Tan

#### Certifications Available:

ANSI and FEPA  
Agency and Mil-specs

#### Typical Bulk Density (g/cm<sup>3</sup>):

Grit	BD	Grit	BD
8	2.03-2.13	60	1.74-1.88
10	1.97-2.12	70	1.72-1.86
12	1.94-2.09	80	1.71-1.85
14	1.92-2.07	90	1.67-1.81
16	1.90-2.05	100	1.64-1.78
20	1.87-2.03	120	1.63-1.77
24	1.85-1.99	150	1.62-1.76
30	1.81-1.95	180	1.60-1.72
36	1.79-1.93	220	1.58-1.72
46	1.77-1.91	240	1.56-1.70
54	1.76-1.90		

#### Typical Chemical Analysis:

Mineral	%
Aluminum Oxide	96.69 %
Titanium Dioxide (TiO <sub>2</sub> )	2.52 %
Silicon Dioxide (SiO <sub>2</sub> )	0.44 %
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	0.10 %
Others (MgO, CaO, Cr <sub>2</sub> O <sub>3</sub> )	< 0.1