



**YOUR COMPLETE FINISHING
SOLUTIONS RESOURCE**

PREPARATION AND PRE-TREATMENT

POWDER COATING

LIQUID PAINTING

CURING AND DRYING


COMPONENTS

CONTROLS



SurfacePrep


INDUSTRIAL BLAST ENCLOSURE



STANDARD FEATURES

- Premium 12 gauge G90 galvanized steel cabin
- 4" companion flanges, seams with urethane dust tight seal
- Heavy gauge structural ribs and stiffeners
- Inlet and exhaust air media baffles
- Acrylic light lens covers
- Safety door interlock limit switches


INDUSTRIAL WASH ENCLOSURE



STANDARD FEATURES

- Baffled exhaust plenum with moisture eliminating mesh filters
- Aluminum mesh intake filters
- UL listed moisture rated light fixtures
- UL 508 listed control panel
- Non-fused service disconnect
- NEMA 12 Industrial Enclosure
- Motor protection
- 12" containment
- Auto booth pressure/velocity control

IN-LINE PROCESS WASHER



STANDARD FEATURES

- Stainless steel tanks and canopy
- CPVC risers with quick connect clamps
- Slopped tanks for easy cleaning
- Vertical process pumps with TEFC motors
- Tank level control and automatic counter flow
- Entrance and exit moisture ventilation fans

POWDER COATING

BATCH NON-RECOVERY BOOTH



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel construction
- Rear access not required for maintenance
- High efficiency airfoil blower with TEFC motor
- Blanket over pocket primary filtration and MERV 13 final filters
- Safe quiet operation < 83db @ 5'
- High-efficiency, color-correct, LED light fixtures


BATCH CARTRIDGE RECOVERY BOOTH



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel (powder coat white recommended)
- Smooth interior surface for easy cleaning. Nuts and Bolts are mounted on the exterior
- Expandable for future growth
- Quiet blower with TEFC direct drive motor operated by VFD
- High-efficiency, color-correct, LED light fixtures

IN-LINE PROCESS RECOVERY BOOTH



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel (powder coat white optional)
- Roll-away quick color change reclaim hopper with fluidized bed
- High static quiet blower with TEFC direct drive motor
- VFD controlled variable volume for maximized transfer efficiency
- Automatic back pulse cleaning
- High-efficiency LED light fixtures
- Horizontal airflow with adjustable velocity


INDUSTRIAL OPEN FACE



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel construction
- AMCA certified aluminum blade fans with TEFC motor standard
- High-efficiency, color-correct, LED light fixtures
- 20x20 Industry standard filters
- 125 F.P.M. standard booth velocity
- Easy nut and bolt assembly with 3D exploded view drawing


CROSSDRAFT BOOTH



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel construction
- AMCA certified aluminum blade fans with TEFC motor standard
- High-efficiency, color-correct, LED light fixtures
- 20x20 Industry standard filters
- 100 F.P.M standard booth velocity
- Welded tube steel doors
- Easy nut & bolt assembly with 3D exploded view drawings

DOWNDRAFT BOOTH




STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel construction
- AMCA certified aluminum blade fans with TEFC motor standard
- High-efficiency, color-correct, LED light fixtures
- 20x20 Industry standard filters
- 200# sq./ft. steel pit grating
- Product doors
- Easy nut & bolt assembly with 3D exploded view drawings

CURING AND DRYING


BATCH OVEN



STANDARD FEATURES

- 4" thick, 20 gauge aluminized panels insulated with 4lbs. density mineral wool, and perforated grooved seams
- Gas-fired 25:1 turn-down process heater for precise control
- UL508A industrial control panel with HMI touchscreen user interface
- Welded formed steel product doors and heavy-duty hinges with bearings
- 12 gauge aluminized cold formed sheet steel frames, no field welding required
- Mixed airflow with filtered supply air
- Superior temperature uniformity

PROCESS OVEN



STANDARD FEATURES

- 4" thick, 20 gauge aluminized panels insulated with 4lbs. density mineral wool, and perforated grooved seams
- Gas-fired 25:1 turn-down process heater for precise control
- UL508A industrial control panel with HMI touchscreen user interface
- Welded formed steel product doors and heavy-duty hinges with bearings
- 12 gauge aluminized cold formed sheet steel frames, no field welding required
- Mixed airflow with filtered supply air
- High velocity powered heat retention air curtain


POWDER RECOVERY COLLECTOR



STANDARD FEATURES

- 12-14 gauge powder coated housing
- Safe quiet operation < 83db @ 5'
- Industrial UL listed control panel with blower VFDs (standard)
- Reclaim drawer (standard), fluidized reclaim hopper (standard)
- 99.9% efficient 80/20 nano-fiber filters
- Automatic Back Pulse Cleaning
- Redundant second stage filters
- Pre-wired control panel

RECLAIM MODULE



STANDARD FEATURES

- 14-12 gauge powder coated housing
- Safe quiet operation < 83db @ 5'
- Industrial UL listed control panel with blower VFDs (standard)
- 150lb fluidized reclaim hopper
- 99.9% efficient 80/20 Nano-fiber filters
- Automatic Back Pulse Cleaning
- Redundant second stage filters
- Pre-wired control panel

DUST COLLECTOR




STANDARD FEATURES

- Electro-galvanized steel powder coated for maximum corrosion resistance
- Factory mounted high efficiency direct drive blower
- Rohner automatic variable speed VFD motor control
- Factory piped automatic back pulse with down time cleaning
- Drum adapter kit with manual slide
- Down-flow cartridge collector
- Automatic back pulse cleaning

CONTROLS

PAINT MIX ROOM



STANDARD FEATURES

- Premium 18 gauge G90 galvanized steel construction
- Quiet blower with explosion-proof motor
- Filtered intake air
- High-efficiency, color-correct, LED light fixtures
- Large access door, 3ft. x 7ft., with tempered observation window
- Built-in spill containment
- Paint storage area and work bench
- Easy field installation

OPERATOR PROCESS CONTROL



STANDARD FEATURES

- UL listed industrial controls
- 5.7" QVGA color touch screen
- NEMA 12 main PLC enclosure
- Industrial start/mode & stop buttons
- F.L.O. = "Filter Life Optimizer"
- Automatic booth pressure balance
- System status/diagnostics troubleshooter
- Multi-stage ramp and recipe memory for flash, bake, and cool down

F.L.O.



STANDARD FEATURES

- UL listed industrial controls
- NEMA 12 main enclosure
- Industrial start/stop buttons
- Automatic booth pressure or velocity control
- Clogged filter alarm
- Filter life warning indicator
- F.L.O. user-adjustable set points accommodate use of all exhaust filter brands



LOOK TO ROHNER FOR CUSTOM SOLUTIONS

ASSEMBLY AND INSTALLATION SERVICES

AUTOMATED HANDLING AND CONVEYOR SYSTEMS

AIR HANDLING WITH TEMPERATURE AND HUMIDITY
CONTROL

AEROSPACE AND MILITARY CORROSION CONTROL
FACILITIES

2650 NE Andresen Rd. #102 Vancouver, WA 98661

Toll Free (888) 885-7641 • rohnerspraybooths.com

Ph. (360) 885-7641 • email: info@rohner-usa.com

